

# Varitile Mistral

## The stately aesthetics of **European styling**


Varitile Mistral combines the benefits of steel roofing with classic European styling. Enhance your roofline with Varitile's strong, lightweight, virtually maintenance free Mistral tile.



Varitile®

weather [p]roof

# www.varitile.com



WIND

HAIL

# **Varitile Mistral**


Formed from the highest quality steel and protective coatings, Varitile is incredibly strong, lightweight and weather resistant.

16.34" [415 mm] (Cover 14.57" [370 mm])



#### INSTALLATION

Mistral can be installed left to right or right to left. For maximum visual appeal and performance, stagger at least one pan width.



#### **SPECIFICATIONS**

Minimum pitch	2/12	[10°]
Maximum pitch	vertical	[90°]
Size of tile - overall*	51.38" x 16.34"	[1305 x 415 mm]
Size of tile - cover*	48.82" x 14.57"	[1240 x 370 mm]
Gauge of steel**	26 gauge ZA300	[0,45 mm ZA300]
Linear cover width*	48.82"	[1240 mm]
Tiles per square	20.25 pc	[2,18 pc/m <sup>2</sup> ]
Weight per square*	134 pounds	[6,54 kg/m <sup>2</sup> ]
Weight per tile*	6.61 pounds	[3,00 kg]

\* The measurements and the weight may vary slightly by the finish that is added to the panel. \*\* Steel thickness according to the EN 10346.

### STANDARD COLORS



More colors available. Ask your dealer for information. Panels are placed on nominal 2x2 wood battens spaced 14.5" [368mm].

A downturned front edge (nose) and upturned rear edge (shelf) on each tile creates a strong, weatherproof, overlapping and interlocking assembly. Each tile is secured with four nails in the panel nose, away from water channels.

#### ACCESSORIES

Varitile offers a broad range of accessories.

- Ridges, junctions and end caps. Offered in angled, squared and curved profiles.
- Fascia, sidewall and headwall transition flashings.
- Ventilation systems.
- Installation Equipment: nails, benders, guillotines. It is important to use tools recommended by Varitile.

For a complete and detailed list of accessories and more information regarding the installation of a Varitile roof, contact your dealer.