

### Varitile Shake

### Warm wooden roofs without the need for regular treatment

Varitile Shake, is a perfect imitation of traditional hand-split wooden shakes with a natural, rustic look, ideal for discerning property owners.





# www.varitile.com

#### WIND

HAIL

### **ENERGY**

LIGHTNING

IMPENETRABLE EARTHQUAKE

FIRE

## Varitile Shake

Formed from the highest quality steel and protective coatings, Varitile is incredibly strong, lightweight and weather resistant.



### **SPECIFICATIONS**

Minimum pitch	2/12	[10°]
Maximum pitch	vertical	[90°]
Size of tile - overall*	52.36" x 16.34"	[1330 x 415 mm]
Size of tile - cover*	49.80" x 14.57"	[1265 x 370 mm]
Gauge of steel**	26 gauge ZA300	[0,45 mm ZA300]
Linear cover width*	49.80"	[1265 mm]
Tiles per square	19.85 pc	[2,14 pc/m <sup>2</sup> ]
Weight per square*	132 pounds	[6,41 kg/m²]
Weight per tile*	6.61 pounds	[3,00 kg]

\* The measurements and the weight may vary slightly by the finish that is added to the panel. \*\* Steel thickness according to the EN 10346.

### STANDARD COLORS



More colors available. Ask your dealer for information.

#### INSTALLATION

Shake can be installed left to right or right to left. A 13 inch (330mm) offset provides maximum visual appeal and performance.



Panels are placed on nominal 2x2 wood battens spaced 14.5" [368mm].

A downturned front edge (nose) and upturned rear edge (shelf) on each tile creates a strong, weatherproof, overlapping and interlocking assembly. Each tile is secured with four nails in the panel nose, away from water channels.

### ACCESSORIES

Varitile offers a broad range of accessories.

- Ridges, junctions and end caps. Offered in angled, squared and curved profiles.
- Fascia, sidewall and headwall transition flashings.
- Ventilation systems.
- Installation Equipment: nails, benders, guillotines. It is important to use tools recommended by Varitile.

For a complete and detailed list of accessories and more information regarding the installation of a Varitile roof, contact your dealer.