

Varitile® weather [p]roof

www.varitile.com

* Not available in North America markets

An authentic Mediterranean look for your home.

Varitile Roman's robust aesthetics and minimal weight bring the charm of Mediterranean clay tile roofs to any structure. A heart of Zinc-Aluminium coated steel with advanced stone granule coating guarantees optimal protection for your home without the weight, cracking and breakage associated with clay and concrete roofs.

















HAIL

FREEZE/THAW

ENERGY


IMPENETRABLE EARTHQUAKE

FIRE

Varitile Roman*

* Not available in North America markets

Formed from the highest quality steel and protective coatings, Varitile is incredibly strong, lightweight and weather resistant.



SPECIFICATIONS

Minimum pitch	2/12	[10°]
Maximum pitch	vertical	[90°]
Size of tile - overall*	50.39" x 16.34"	[1280 x 415 mm]
Size of tile - cover*	48.03" x 14.57"	[1220 x 370 mm]
Gauge of steel**	26 gauge ZA300	[0,45 mm ZA300]
Linear cover width*	48.03"	[1220 mm]
Tiles per square	20.60 pc	[2,22 pc/m ²]
Weight per square*	136 pounds	[6,65 kg/m ²]
Weight per tile*	6.61 pounds	[3,00 kg]

^{*} The measurements and the weight may vary slightly by the finish that is added to the panel.

STANDARD COLORS










More colors available. Ask your dealer for information.

INSTALLATION

Roman tiles are overlapped right to left. For maximum visual appeal and performance, stagger at least one pan width.



Panels are placed on nominal 2x2 wood battens spaced 14.5" [368mm].

A downturned front edge (nose) and upturned rear edge (shelf) on each tile creates a strong, weatherproof, overlapping and interlocking assembly. Each tile is secured with four nails in the panel nose, away from water channels.

ACCESSORIES

Varitile offers a broad range of accessories.

- Ridges, junctions and end caps.
 Offered in angled, squared and curved profiles.
- Fascia, sidewall and headwall transition flashings.
- Ventilation systems.
- Installation Equipment: nails, benders, guillotines. It is important to use tools recommended by Varitile.

For a complete and detailed list of accessories and more information regarding the installation of a Varitile roof, contact your dealer.

[&]quot;Steel thickness according to the EN 10346