

* Not available in US, Canada and Mexico

Varitile® weather [p]roof

A traditional and attractive roof with timeless effect

The Bond provides traditional beavertail clay tile aesthetics without the concerns of heavy weight and tile breakage. Eight pans combine in a single panel, thereby providing maximum coverage and reducing labor expense.

















WIND

HAIL

FREEZE/THAW

ENERGY

LIGHTNING IMPENETRABLE EARTHQUAKE


FIRE

www.varitile.com

Bond

Formed from the highest quality steel and protective coatings, the panel is incredibly strong, lightweight and weather resistant.

SPECIFICATIONS




Minimum pitch	10°	2/12
Maximum pitch	90°	vertical
Size of tile - overall*	1335 x 415 mm	52.64" x 16.34"
Size of tile - cover*	1270 x 370 mm	50" x 14.57"
Gauge of steel**	0,45 mm	26 gauge
Linear cover width*	1270 mm	50"
Coverage*	2,13 pc/m ²	19.77 pc/square
Coverage of a panel*	0,47 m ²	5.06 ft ²
Weight per panel*	2,94 kg	6.49 lb

 $^{^{\}ast}$ With a tolerance of $\pm\,3$ mm on measurements and minimal tolerance in weight.

INSTALLATION

Bond can be installed left to right or right to left.



The panels are placed onto battens spaced 14.5" or 368mm.

A downturned front edge (nose) and upturned rear edge (shelf) on each tile creates a strong, weatherproof, overlapping and interlocking assembly. Each tile is secured with four nails in the panel nose, away from water channels.

COLORS



You can mix and match the wide color palette and profile to create something unique. With the special shades you create the perfect tones for your house.

Ask your dealer for more information regarding stock colors and leadtimes for special color and profile combinations.

ACCESSORIES

We offer a broad range of accessories.

- Ridges, junctions and end caps.
 Offered in angled, squared and curved profiles.
- Fascia, sidewall and headwall transition flashings.
- Ventilation systems.
- Installation Equipment: nails, benders, guillotines.
 It is important to use tools recommended by us.

For a complete and detailed list of accessories and more information regarding the installation of a Bond roof, contact your dealer.

[&]quot;Steel thickness according to the EN 10346.