

Varitile®
weather [p]roof



iShingle

**A wood shingle aesthetic without
the fire risk**

Beauty is not the only benefit of the iShingle these interlocking steel shingles are fire, hail and wind resistant.



WIND



HAIL



FREEZE/THAW



ENERGY



LIGHTNING



IMPENETRABLE



EARTHQUAKE




FIRE

www.varitile.com

iShingle

Formed from the highest quality steel and protective coatings, the panel is incredibly strong, lightweight and weather resistant.

SPECIFICATIONS



Minimum pitch	10°	2/12
Maximum pitch	90°	vertical
Size - overall*	1340 x 430 mm	52.76" x 16.93"
Size - cover*	1230 x 375 mm	48.43" x 14.76"
Gauge of steel**	0,45 mm	26 gauge
Linear cover width*	1230 mm	48.43"
Cover*	2,17 pc/m ²	20.14 pc/square
Cover of a panel*	0,46 m ²	4.96 ft ²
Weight per panel*	3,29 kg	7.26 lb

* With a tolerance of ± 3 mm on measurements and minimal tolerance in weight.

** Steel thickness according to the EN 10346.

COLORS




Color has a huge impact on the look of your house. Whether it is neutral shades, vibrant tones or subtle hues, there is something for everyone.

You can mix and match the wide color palette and profile to create something unique. With the special shades you create the perfect tones for your house.

Ask your dealer for more information regarding stock colors and leadtimes for special color and profile combinations.

INSTALLATION

The iShingle is installed from right to left and from bottom to top.



The panels are placed onto deck spaced 14.5" or 368 mm.

The panels are simply connected by the use of an interlocking groove that creates a strong, weatherproof and overlapping assembly. They are fixed onto the framework, before interlocking the panel above, so that no nail or screw heads are visible after the panels are assembled.

ACCESSORIES

We offer a broad range of accessories.

- Ridges, junctions and end caps.
Offered in angled, squared and curved profiles.
- Fascia, sidewall and headwall transition flashings.
- Ventilation systems.
- Installation Equipment: nails, benders, guillotines.
It is important to use tools recommended by us.

For a complete and detailed list of accessories and more information regarding the installation of a iShingle roof, contact your dealer.